

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

ABSTRACT

An arc tube for a discharge bulb is provided for use in a vehicular lighting system. The arc tube includes a closed glass bulb that is pinch-sealed at opposite ends. Inner ends of a first
5 electrode and a second electrode extend into the closed glass bulbs from the ends of the closed glass bulb. The atmosphere inside the closed glass bulb includes a starting rare gas, a primary light-emitting metal halide; and optionally, a buffer
10 metal halide. The distance between the inner ends of the electrodes is between about 0.3 and 1.8, and the inner diameter of the closed glass bulb at a middle portion is between about 1.5 mm and 2.7 mm. Accordingly, a stable discharge is produced using between 15W and 30W of power.